NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WARTIME REPORT

ORIGINALLY ISSUED
March 1944 as
Advance Confidential Report L4C24

ON THE FLOW OF A COMPRESSIBLE FLUID

BY THE HODOGRAPH METHOD

I - UNIFICATION AND EXTENSION OF PRESENT-DAY RESULTS

By I. E. Garrick and Carl Kaplan

Langley Memorial Aeronautical Laboratory
Langley Field, Va.

NACA

WASHINGTON

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

ADVANCE CONFIDENTIAL REPORT NO. L4C24

ON THE FLOW OF A COMPRESSIBLE FLUID

BY THE HODOGRAPH METHOD

I - UNIFICATION AND EXTENSION OF PRESENT-DAY RESULTS

By I. E. Garrick and Carl Kaplan

SUMMARY

Elementary basic solutions of the equations of
motion of a compressible fluid in the hodograph variables
are developed and used to provide a basis for comparison,
in the form of velocity correction formulas, of corre-
sponding compressible and incompressible flows. The
known approximate results of Chaplygin, von Kármán and
Tsien, Temple and Yarwood, and Prandtl and Glauert are
unified by means of the analysis of the present paper.
Two new types of approximations, obtained from the basic
solutions, are introduced; they possess certain desirable
features of the other approximations and appear prefera-
ble as a basis for extrapolation into the range of high
stream Mach numbers and large disturbances to the main
stream. Tables and figures giving velocity and pressure-
coefficient correction factors are included in order to
facilitate the practical application of the results.

INTRODUCTION

The present paper is concerned with a theoretical
study of the hydrodynamical equations of a perfect com-
pressible fluid in two dimensions, in which the so-called
hodograph variables are used as the independent variables.
It is hoped to achieve herein a unification of the
present-day results obtained in this field and also to
provide a working basis for further developments. The
earliest contributors to the hodograph method for treating
compressible fluids were Molenbroek (reference 1) and
Chaplygin (reference 2). The remarkable work of
Chaplygin on gas jets appeared in Russian in 1904 but re-
mained relatively unnoticed. In recent years contribu-
tions to the hodograph method have been made chiefly by

2   CONFIDENTIAL   NACA ACR No. L4C24

Demtchenko (reference 3), von Kármán (reference 4), Tsien
(reference 5), Ringleb (reference 6), and Temple and
Yarwood (reference 7).

The chief reason, and perhaps the only reason, for
preferring the hodograph variables to the physical plane
coordinates is that the equations of motion in the
hodograph variables are linear. This simplification is
achieved, however, at the cost of more difficult boundary
conditions and at a loss of physical insight. The great
simplification in the mathematics due to linearity never-
theless makes it desirable to pursue this line of attack
as long as it appears profitable to do so.

The mathematics for handling the flow equations re-
ceived a substantial impetus by the work of Bers and
Gelbart (reference 8), who developed a new function theory
analogous to ordinary analytic function theory. The
present paper utilizes the methods of this new function
theory to develop certain functions essential to the
compressible-flow problem. It is of historical interest
that ideas similar to those of Bers and Gelbart were ex-
plored by the renowned mathematician Hilbert (reference 9)
in the early part of this century but do not appear to
have been further developed at the time.

The material to be treated is conveniently separated
into two parts. In part I, the present paper, basic
particular solutions of the hodograph flow equations are
developed and employed in unifying and extending the re-
sults obtained by Chaplygin, von Kármán, and Temple and
Yarwood. The results obtained in part I are of immediate
practical application and are given in the form of tables
and graphs of velocity and pressure-coefficient correction
factors. In part II, which will appear later, general
particular solutions of the hodograph flow equations are
developed and discussed. The material in part II, it
is hoped, will lead to a method for handling the actual
boundary problem of the flow of a compressible fluid past
a prescribed body.

ANALYSIS

Flow Equations of an Incompressible Fluid

It is well known that the relations between the
velocity potential ϕ and the stream function ψ for

the steady irrotational two-dimensional motion of a
perfect incompressible fluid are

$$\left. \begin{array}{l} \dfrac{\partial \phi}{\partial x} = \dfrac{\partial \psi}{\partial y} \\[4mm] \dfrac{\partial \phi}{\partial y} = -\dfrac{\partial \psi}{\partial x} \end{array} \right\} \qquad (1)$$

These equations are the Cauchy-Riemann equations and
therefore $\phi + i\psi$ is an analytic function $f(z)$ of the
complex variable $z = x + iy$.

The complex velocity or reflected velocity vector
$u - iv$ is obtained from the complex potential $f(z)$ by
differentiation.   Thus,

$$u - iv = \frac{df(z)}{dz}$$

$$= qe^{-i\theta}$$

$$= e^{-i(\theta + i \log q)} \qquad (2)$$

where q is the magnitude of the velocity vector and θ
is the angle the vector makes with the positive direction
of the x-axis.

The variables θ and q are sometimes referred to
as "the hodograph variables."   The flow equations in the
variables θ and q can be readily derived by intro-
ducing $\theta + i \log q$ as the independent complex variable
in place of $x + iy$.   Then, in analogy with equation (1),

$$\left. \begin{array}{l} \dfrac{\partial \phi}{\partial \theta} = \dfrac{\partial \psi}{\partial \log q} \\[4mm] \dfrac{\partial \phi}{\partial \log q} = -\dfrac{\partial \psi}{\partial \theta} \end{array} \right\} \qquad (3)$$

or

$$\left.\begin{array}{l} \dfrac{\partial \phi}{\partial \theta} = q \, \dfrac{\partial \psi}{\partial q} \\[2ex] \dfrac{\partial \phi}{\partial q} = -\dfrac{1}{q} \, \dfrac{\partial \psi}{\partial \theta} \end{array}\right\} \tag{4}$$

These equations are known as the hodograph equations for the flow of an incompressible fluid.

Flow Equations of a Compressible Fluid

The equations corresponding to equation (1) are, for a compressible fluid,

$$\left.\begin{array}{l} \dfrac{\partial \phi}{\partial x} = \dfrac{\rho_0}{\rho} \, \dfrac{\partial \psi}{\partial y} \\[2ex] \dfrac{\partial \phi}{\partial y} = -\dfrac{\rho_0}{\rho} \, \dfrac{\partial \psi}{\partial x} \end{array}\right\} \tag{5}$$

where ρ is the density of the fluid at any point (x,y) and ρ_0 is a constant density, which for convenience is referred to a stagnation point.

A short way to derive the hodograph equations for a compressible fluid, attributed to Molenbroek, is as follows:

According to equation (5), with $u = \dfrac{\partial \phi}{\partial x}$ and $v = \dfrac{\partial \phi}{\partial y}$

$$d\phi + i \, \frac{\rho_0}{\rho} \, d\psi = (u \, dx + v \, dy) + i(-v \, dx + u \, dy)$$

$$= (u - iv)(dx + i \, dy)$$

$$= qe^{-i\theta} \, dz$$

or

$$dz = \frac{1}{q} \, e^{i\theta} \left(d\phi + i \, \frac{\rho_0}{\rho} \, d\psi \right) \tag{6}$$

It follows from equation (6), by considering θ and q as independent variables, that

$$\frac{\partial z}{\partial \theta} = \frac{1}{q} \, e^{i\theta}\left(\frac{\partial \phi}{\partial \theta} + i \, \frac{\rho_o}{\rho} \, \frac{\partial \psi}{\partial \theta}\right)$$

and

$$\frac{\partial z}{\partial q} = \frac{1}{q} \, e^{i\theta}\left(\frac{\partial \phi}{\partial q} + i \, \frac{\rho_o}{\rho} \, \frac{\partial \psi}{\partial q}\right)$$

Then, by assuming that ρ is a function of only q (equivalent to assuming that the pressure is a function of only the density),

$$\frac{\partial^2 z}{\partial q \, \partial \theta} = e^{i\theta}\left[-\frac{1}{q^2} \frac{\partial \phi}{\partial \theta} + i \, \frac{d(\rho_o/\rho q)}{dq} \, \frac{\partial \psi}{\partial \theta}\right] + \frac{1}{q} \, e^{i\theta}\left(\frac{\partial^2 \phi}{\partial q \, \partial \theta} + i \, \frac{\rho_o}{\rho} \, \frac{\partial^2 \psi}{\partial q \, \partial \theta}\right)$$

and

$$\frac{\partial^2 z}{\partial \theta \, \partial q} = \frac{i}{q} \, e^{i\theta}\left(\frac{\partial \phi}{\partial q} + i \, \frac{\rho_o}{\rho} \, \frac{\partial \psi}{\partial q}\right) + \frac{1}{q} \, e^{i\theta}\left(\frac{\partial^2 \phi}{\partial \theta \, \partial q} + i \, \frac{\rho_o}{\rho} \, \frac{\partial^2 \psi}{\partial \theta \, \partial q}\right)$$

Since, by continuity, these two expressions are identical, it follows that

$$\frac{i}{q} \, e^{i\theta}\left(\frac{\partial \phi}{\partial q} + i \, \frac{\rho_o}{\rho} \, \frac{\partial \psi}{\partial q}\right) = e^{i\theta}\left[-\frac{1}{q^2} \frac{\partial \phi}{\partial \theta} + i \, \frac{d(\rho_o/\rho q)}{dq} \, \frac{\partial \psi}{\partial \theta}\right]$$

Hence, by equating real and imaginary parts,

$$\left.\begin{array}{c}\dfrac{\partial \phi}{\partial \theta} = \dfrac{\rho_o q}{\rho} \, \dfrac{\partial \psi}{\partial q} \\[3ex] \dfrac{\partial \phi}{\partial q} = q \, \dfrac{d(\rho_o/\rho q)}{dq} \, \dfrac{\partial \psi}{\partial \theta}\end{array}\right\} \qquad (7)$$

These are the hodograph equations, first obtained by
Molenbroek, for the flow of a compressible fluid and are
independent of the form of the pressure-density relation.
It is observed that, when $\rho = \rho_0 = $ Constant, equa-
tions (7) reduce to equations (4).   Equations (7), in
contrast with equations (5), are linear in the dependent
variables.

Bernoulli's Equation and Equation of State

In the present section there is listed a collection
of formulas and definitions necessary in the analysis.

Bernoulli's equation for a compressible fluid is

$$\int_{p_0}^{p} \frac{dp}{\rho} + \frac{1}{2} q^2 = 0 \qquad (8)$$

where

p   static pressure in fluid

p_0 static pressure at stagnation point (q = 0)

ρ density of fluid

q   magnitude of velocity of fluid

The adiabatic relation between the pressure and the
density is

$$\frac{p}{p_0} = \left(\frac{\rho}{\rho_0} \right)^{\gamma} \qquad (9)$$

where

γ adiabatic index (approx. 1.4 for air)

ρ_0 density of fluid at stagnation point (q = 0)

The local velocity of sound a is obtained from

$$a^2 = \frac{dp}{d\rho}$$

For the adiabatic case,

$$a^2 = \gamma \frac{p}{\rho} \tag{10}$$

From Bernoulli's equation (8) and from equations (9) and (10), the following relations may be obtained:

$$\left.\begin{aligned}
a^2 &= a_o{}^2 - \frac{1}{2}(\gamma - 1)q^2 \\[2ex]
\rho &= \rho_o\left[1 - \frac{1}{2}(\gamma - 1)\frac{q^2}{a_o{}^2}\right]^{\frac{1}{\gamma-1}} \\[2ex]
p &= p_o\left[1 - \frac{1}{2}(\gamma - 1)\frac{q^2}{a_o{}^2}\right]^{\frac{\gamma}{\gamma-1}}
\end{aligned}\right\} \tag{11}$$

where a_o is the velocity of sound at stagnation point $(q = 0)$.

From equations (11), for $\gamma > 1$, a maximum velocity $q = q_m$ is obtained for the limiting conditions $p = \rho = a = 0$. Thus,

$$\begin{aligned}
q_m{}^2 &= \frac{2}{\gamma - 1} a_o{}^2 \\[2ex]
&= 2\beta a_o{}^2
\end{aligned} \tag{12}$$

where

$$\beta = \frac{1}{\gamma - 1}$$

The fundamental nondimensional speed variable, in general, is q/a_o but it is found useful in the analysis to employ a nondimensional speed variable τ defined as

$$\tau = q^2/q_m{}^2 \tag{13}$$

For $\gamma > 1$, the range of the variable τ is $0 \leqq \tau \leqq 1$. The value $\tau = 0$ has a dual meaning; $\tau = 0$ in the case

of a compressible fluid corresponds to a stagnation point $(q = 0)$, or $\tau = 0$ may mean the limiting case of an incompressible fluid $(a_0 = \infty)$.

With the definitions of τ' and β, equations (11) become

$$
\left.
\begin{aligned}
a &= a_0(1 - \tau)^{1/2} \\
\rho &= \rho_0(1 - \tau)^{\beta} \\
p &= p_0(1 - \tau)^{\beta+1}
\end{aligned}
\right\} \tag{14}
$$

The local Mach number $M = q/a$ may be expressed in terms of the speed variable τ in the following way:

$$
M^2 = \frac{q^2}{q_m{}^2}\frac{q_m{}^2}{a_0{}^2}\frac{a_0{}^2}{a^2}
$$

$$
= \frac{2\beta\tau}{1 - \tau} \tag{15}
$$

or, by solving for τ in terms of M,

$$
\tau = \frac{M^2}{2\beta + M^2} \tag{16}
$$

The value of τ for which the local velocity of the fluid equals the local velocity of sound $(M = 1)$ is given by

$$
\tau_s = \frac{1}{2\beta + 1} \tag{17}
$$

In the case of uniform flow past a fixed boundary, the pressure coefficient is defined as

$$
C_{p,M_1} = \frac{p - p_1}{\frac{1}{2}\rho_1 q_1{}^2}
$$

where the subscript 1 refers to the undisturbed stream. The pressure coefficient for the incompressible case (M = 0) is

$$C_{p,o} = 1 - \left(\frac{q}{q_1}\right)_i^2 \tag{18a}$$

The pressure coefficient for the compressible case is

$$C_{p,M_1} = \frac{2}{\gamma M_1^2}\left(-1 + \left\{1 + \frac{1}{2}(\gamma - 1)M_1^2\left[1 - \left(\frac{q}{q_1}\right)_c^2\right]\right\}^{\frac{\gamma}{\gamma-1}}\right) \tag{18b}$$

For q = q_s (sonic),

$$\left(C_{p,M_1}\right)_s = \frac{2}{\gamma M_1^2}\left\{-1 + \left[\frac{2 + (\gamma - 1)M_1^2}{\gamma + 1}\right]^{\frac{\gamma}{\gamma-1}}\right\} \tag{18c}$$

For q = q_m (vacuum),

$$\left(C_{p,M_1}\right)_m = -\frac{2}{\gamma M_1^2} \tag{18d}$$

Basic Solutions of Hodograph Equations

Consider the incompressible case represented by equations (3) or (4). It is clear that $\phi = \theta$ and $\psi = \log q$ satisfy these equations. In fact, any convergent power series in $w = \theta + i \log q$ represents an analytic function of which the real and imaginary parts satisfy equations (3) or (4). The class of analytic functions in w (and the concept of analytic continuation) then yields all the particular solutions of these equations.

The particular solution $w = \theta + i \log q$ can be obtained by means of an integration that is instructive in the generalization to the compressible case. It is well known that

$$F(w) = \int f(w) \, dw$$

can be represented as the sum of two line integrals

$$F(w) = \int (P \, d\theta - Q \, d\log q) + i \int (Q \, d\theta + P \, d\log q)$$

where

$$f(w) = P + iQ$$

Thus, given a pair of functions P and Q that satisfy equations (3) or (4), this process yields another pair of solutions, namely, the real and the imaginary parts of $F(w)$. For example, if $P = 1$ and $Q = 0$,

$$F(w) = w = \theta + i \log q \qquad (19)$$

Again, if $P = 0$ and $Q = 1$,

$$F(w) = iw = -\log q + i\theta \qquad (20)$$

The physical interpretation of equations (19) and (20), considered as flow patterns, is of some interest in connection with later developments. It is clear that equations (19) and (20) represent a vortex and a source located at the origin, respectively.

The generalization to the compressible case of the foregoing elementary results was accomplished by Bers and Gelbart (reference 8) by means of simple yet fertile ideas. Bers and Gelbart treat equations of the form

$$\left. \begin{aligned} \frac{\partial \phi}{\partial \theta} &= \lambda_1(q) \, \frac{\partial \psi}{\partial q} \\[2mm] \frac{\partial \phi}{\partial q} &= -\lambda_2(q) \, \frac{\partial \psi}{\partial \theta} \end{aligned} \right\} \qquad (21)$$

and show as is readily verified that, if P and Q are a pair of solutions, the real and imaginary parts of the following sum of line integrals

$$\int \left[P\ d\theta - \lambda_2(q)\ Q\ dq \right] + i \int \left[Q\ d\theta + \frac{1}{\lambda_1(q)}\ P\ dq \right] \qquad (22)$$

are also solutions of equations (21).

In particular, corresponding to the pair of solutions $P = 1$ and $Q = 0$, there is obtained

$$W = \theta + i \int \frac{1}{\lambda_1(q)}\ dq \qquad (23)$$

and, for $P = 0$ and $Q = 1$,

$$i\tilde{W} = i \left[\theta + i \int \lambda_2(q)\ dq \right] \qquad (24)$$

By repeated application of the process of integration, indicated by expression (22), a general set of particular solutions of equations (21) may be obtained. These particular solutions are discussed in part II; in the present paper, only the solutions given by equations (23) and (24) are needed.

The general hodograph equations (7) are of the form of equations (21) with

$$\lambda_1(q) = \frac{\rho_0 q}{\rho}$$

and

$$\lambda_2(q) = -q\ \frac{d(\rho_0/\rho q)}{dq}$$

For the rest of this paper, the adiabatic pressure-density relation (9) is used. By means of equations (9) and (14) and the relation

$$\frac{d\rho}{dq} = -\frac{\rho}{q}\ M^2$$

and

$$g(\tau) = \frac{1}{2} \int_0^\tau \left[\frac{1 - 6\tau}{(1 - \tau)^{7/2}} - 1 \right] \frac{d\tau}{\tau}$$

$$= - \frac{1}{(1 - \tau)^{5/2}} + \frac{1}{3} \frac{1}{(1 - \tau)^{3/2}}$$

$$+ \frac{1}{(1 - \tau)^{1/2}} - \frac{1}{3} - \log \frac{1 + (1 - \tau)^{1/2}}{2} \qquad (29)$$

Table 1 contains values of $f(\tau)$ and $g(\tau)$, and figure 1(a) shows these functions plotted against τ. Observe that $f(\tau)$ and $g(\tau)$ are well-behaved functions in the range $0 \leqq \tau < 1$. In figure 1(b), these functions are plotted against the local Mach number M in the practical speed range.

Other interesting cases for which the functions $f(\tau)$ and $g(\tau)$ can be expressed in closed forms are $\gamma = \infty$, $\gamma = 2$, $\gamma = 3/2$, and $\gamma = -1$. For $\gamma = \infty$ ($\beta = 0$, $a = \infty$, incompressible case),

$$f(\tau) = g(\tau) = 0$$

For $\gamma = 2$ ($\beta = 1$),

$$f(\tau) = -\frac{1}{2} \tau$$

$$g(\tau) = 1 - \frac{1}{1 - \tau} - \frac{1}{2} \log (1 - \tau)$$

For $\gamma = \frac{3}{2}$ ($\beta = 2$)

$$f(\tau) = -\tau + \frac{1}{4} \tau^2$$

$$g(\tau) = \frac{1}{2} - \frac{1}{2} \frac{1 + \tau}{(1 - \tau)^2} - \frac{1}{2} \log (1 - \tau)$$

and it is observed that the functions $f(\tau)$ and $g(\tau)$ vanish for $\tau = 0$.

Equations (23) and (24) can be written in the form

$$W = \theta + iL$$

and

$$i\widetilde{W} = i(\theta + i\widetilde{L})$$

It is important to note that, in the incompressible case, W and $i\widetilde{W}$ reduce to w and iw, since L and $\widetilde{L}$ reduce to $\log q$. Thus, there are in the compressible case two basic functions L and $\widetilde{L}$ corresponding to the one function $\log q$ in the incompressible case. It is of interest to mention that the functions W and $i\widetilde{W}$, considered as flow patterns in a compressible fluid, can again be interpreted as a vortex and a source.

Evaluation of Functions $f(\tau)$ and $g(\tau)$

for Various Values of β

In general, the integrals in equations (26) and (27) representing the functions $f(\tau)$ and $g(\tau)$ are expressible by infinite series. For the important case of air, however, with the adiabatic index γ put equal to 1.4 instead of the usual value 1.408, these functions can be obtained in closed forms. Thus, with $\beta = 2.5$,

$$f(\tau) = \frac{1}{2} \int_{0}^{\tau} \left[(1 - \tau)^{5/2} - 1 \right] \frac{d\tau}{\tau}$$

$$= \frac{1}{5} (1 - \tau)^{5/2} + \frac{1}{3} (1 - \tau)^{3/2}$$

$$+ (1 - \tau)^{1/2} - \frac{23}{15} - \log \frac{1 + (1 - \tau)^{1/2}}{2} \qquad (28)$$

and

$$\epsilon(\tau) = \frac{1}{2} \int_0^\tau \left[\frac{1 - 6\tau}{(1 - \tau)^{7/2}} - 1 \right] \frac{d\tau}{\tau}$$

$$= - \frac{1}{(1 - \tau)^{5/2}} + \frac{1}{3} \frac{1}{(1 - \tau)^{3/2}}$$

$$+ \frac{1}{(1 - \tau)^{1/2}} - \frac{1}{3} - \log \frac{1 + (1 - \tau)^{1/2}}{2} \qquad (29)$$

Table 1 contains values of $f(\tau)$ and $g(\tau)$, and figure 1(a) shows these functions plotted against τ. Observe that $f(\tau)$ and $g(\tau)$ are well-behaved functions in the range $0 \leq \tau < 1$. In figure 1(b), these functions are plotted against the local Mach number M in the practical speed range.

Other interesting cases for which the functions $f(\tau)$ and $g(\tau)$ can be expressed in closed forms are $\gamma = \infty$, $\gamma = 2$, $\gamma = 3/2$, and $\gamma = -1$. For $\gamma = \infty$ ($\beta = 0$, $a = \infty$, incompressible case),

$$f(\tau) = g(\tau) = 0$$

For $\gamma = 2$ ($\beta = 1$),

$$f(\tau) = -\frac{1}{2}\tau$$

$$g(\tau) = 1 - \frac{1}{1 - \tau} - \frac{1}{2} \log (1 - \tau)$$

For $\gamma = \frac{3}{2}$ ($\beta = 2$)

$$f(\tau) = -\tau + \frac{1}{4}\tau^2$$

$$g(\tau) = \frac{1}{2} - \frac{1}{2} \frac{1 + \tau}{(1 - \tau)^2} - \frac{1}{2} \log (1 - \tau)$$

For $\gamma = -1$ $\left(\beta = -\frac{1}{2}\right)$,

$$f(\tau) = g(\tau) = - \log \frac{1 + (1 - \tau)^{1/2}}{2}$$

For the isothermal case $\gamma = 1$ $(\beta = \infty)$, the velocity of sound $a = a_0 = $ Constant and the functions f and g are obtained as infinite series in the ratio q/a_0. Thus, in the limit $\beta \longrightarrow \infty$,

$$f\left(q/a_0\right) = \lim_{\beta \to \infty} \frac{1}{2} \int_0^{q/a_0} \left[\left(1 - \frac{q^2}{2\beta a_0{}^2}\right)^\beta - 1\right] \frac{d\left(q/a_0\right)}{q/a_0}$$

$$= \frac{1}{2} \int_0^{q/a_0} \left(e^{-\frac{1}{2}\frac{q^2}{a_0{}^2}} - 1\right) \frac{d\left(q/a_0\right)}{q/a_0}$$

$$= \sum_{n=1}^{\infty} (-1)^n \frac{\left(q^2/a_0{}^2\right)^n}{2^{n+1} \, n \, n!}$$

and

$$g\left(q/a_0\right) = \lim_{\beta \to \infty} \frac{1}{2} \int_0^{q/a_0} \left[\frac{1 - \left(1 + \frac{1}{2\beta}\right)\frac{q^2}{a_0{}^2}}{\left(1 - \frac{q^2}{2\beta a_0{}^2}\right)^{\beta+1}} - 1\right] \frac{d\left(q/a_0\right)}{q/a_0}$$

$$= \frac{1}{2} \int_0^{q/a_0} \left[\left(1 - \frac{q^2}{a_0{}^2}\right) e^{\frac{1}{2}\frac{q^2}{a_0{}^2}} - 1\right] \frac{d\left(q/a_0\right)}{q/a_0}$$

$$= 1 - e^{\frac{1}{2}\frac{q^2}{a_0{}^2}} + \sum_{n=1}^{\infty} \frac{\left(q^2/a_0{}^2\right)^n}{2^{n+1} \, n \, n!}$$

For arbitrary values of γ (or β) the expressions for $f(\tau)$ and $g(\tau)$, obtained with the aid of the binomial expansion, are

$$f(\tau) = \frac{1}{2} \sum_{n=1}^{\infty} (-1)^n \binom{\beta}{n} \frac{\tau^n}{n}$$

$$= -\frac{1}{2} \beta\tau + \frac{1}{8} \beta(\beta - 1)\tau^2 - \ldots$$

$$= -\frac{1}{4} \frac{q^2}{a_0^2} + \frac{1}{32} (2 - \gamma)\left(\frac{q^2}{a_0^2}\right)^2 - \ldots$$

and

$$g(\tau) = -\frac{1}{2} \sum_{n=1}^{\infty} (-1)^n \binom{-\beta}{n} \frac{2n - 1}{n} \tau^n$$

$$= -\frac{1}{2} \beta\tau - \frac{3}{8} \beta(\beta + 1)\tau^2 - \ldots$$

$$= -\frac{1}{4} \frac{q^2}{a_0^2} - \frac{3}{32} \gamma\left(\frac{q^2}{a_0^2}\right)^2 - \ldots$$

The significant feature of this general result is that, if powers of q/a_0 higher than the third are neglected,

$$f(\tau) = g(\tau) \approx -\frac{1}{4} \frac{q^2}{a_0^2} \tag{30}$$

and does not involve explicitly the adiabatic index γ. This circumstance underlies the present-day approximate methods for obtaining velocity and pressure-coefficient correction factors; in the following sections, this point is brought out more clearly.

Application of Basic Functions L and $\tilde{L}$

In this section, the basic functions L and $\tilde{L}$ are employed to set up relations between velocities in "corresponding" compressible and incompressible flows. These relations are of the nature of "stretching factors" or velocity correction formulas and contain the results of Chaplygin, von Kármán, Temple and Yarwood, and Glauert and Prandtl.   It is important to recognize at the outset that no single velocity correction formula can represent in an exact way the correspondence of flow patterns past a prescribed body in a compressible and an incompressible fluid.   A single velocity correction formula is actually feasible in only two cases: (1) The stream Mach number is small (even though the disturbance to the main stream due to the presence of the body may be large) so that the compressible-flow pattern differs only slightly from the incompressible-flow pattern or (2) the disturbance to the main stream is vanishingly small (even though the stream Mach number may be high) so that the effect of the shape of the solid boundary is small.   The various velocity correction formulas discussed in the present paper differ essentially only in the degree to which the requirements of these two cases are satisfied.   Despite their limitations, single velocity correction formulas are extrapolated, in view of the lack of more rigorous solutions, into the range of large disturbances to the main stream and high Mach numbers.   This extrapolation can be justified by further theoretical investigations and by comparison with experimental results.

Consider again the corresponding pairs of functions

$$\left.\begin{array}{l} w = \theta + i \log q \\ W = \theta + iL \end{array}\right\} \tag{31}$$

and

$$\left.\begin{array}{l} iw = i(\theta + i \log q) \\ i\tilde{W} = i(\theta + i\tilde{L}) \end{array}\right\} \tag{32}$$

It has previously been noted that the pairs of functions in equations (31) and (32) denote respectively a vortex and a source in an incompressible and a compressible

fluid.   Each pair of functions can be employed to define
a correspondence of flow patterns in which corresponding
points are identified by the same values (ϕ, ψ).   Thus,
in the case of the vortex (equations (31)),

$$\phi_i = \phi_c = \theta$$

$$\psi_i = \psi_c = \log q_i = L$$

where the subscripts i and c refer to the incompres-
sible and to the compressible case, respectively.   It
follows that

$$q_i = e^L$$

$$= q_c e^{f(\tau)} \tag{33}$$

Similarly, in the case of the source (equations (32)),

$$\phi_i = \phi_c = -\log q_i = -\tilde{L}$$

$$\psi_i = \psi_c = \theta$$

and

$$q_i = e^{\tilde{L}}$$

$$= q_c e^{g(\tau)} \tag{34}$$

At the end of the preceding section it was pointed out
that, to a first approximation, the functions $f(\tau)$ and
$g(\tau)$ are equal.   This fact implies that, to a first
approximation, a single velocity correction formula is
feasible.   The assumption is now made that either equa-
tion (33) or equation (34) can be adopted to provide a
correspondence of flow patterns in the case of uniform
flow past a body in an incompressible and a compressible

fluid. With the undisturbed streams as convenient refer-
ences, the following nondimensional forms of equations (33)
and (34) can be written:

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{e^{f(\tau)}}{e^{f(\tau_1)}} \tag{35}$$

and

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{e^{g(\tau)}}{e^{g(\tau_1)}} \tag{36}$$

where the subscript 1 refers to the undisturbed stream.
The use of the undisturbed stream as reference in the
nondimensional form of the velocity correction formula
was introduced by Tsien in reference 5, where also the
details of the von Kármán approximation are developed.
It is shown in the following section that either of
equations (35) or (36) contains the results of Chaplygin,
von Kármán, and Temple and Yarwood. As has been previ-
ously pointed out, the concept of a single velocity cor-
rection formula is feasible in only two cases, namely,
small stream Mach numbers and vanishingly small disturb-
ances to the main stream. It is desirable then to seek
a single velocity correction formula that combines the
features of these two cases. From this point of view,
equation (35) or equation (36) is not the best choice.
A better choice of a single velocity correction formula
appears to be the following combination of equations (35)
and (36), based on the arithmetic mean of $f(\tau)$ and $g(\tau)$:

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{e^{\frac{1}{2}\left[f(\tau)+g(\tau)\right]}}{e^{\frac{1}{2}\left[f(\tau_1)+g(\tau_1)\right]}} \tag{37}$$

     In a later section, still another combination refer-
red to as "the geometric-mean type of approximation" is
introduced; in the section dealing with the Glauert-Prandtl
approximation, certain features of the foregoing arithmetic-
mean type of approximation and of the geometric-mean type
are discussed.

At this point it is desirable to discuss the practical application of equation (37).   According to equation (16),

$$\tau = \frac{M^2}{2\beta + M^2}$$

$$\tau_1 = \frac{M_1{}^2}{2\beta + M_1{}^2}$$

and

$$\left(\frac{q}{q_1}\right)_c = \left(\frac{\tau}{\tau_1}\right)^{1/2}$$

$$= \frac{M}{M_1}\left(\frac{2\beta + M_1{}^2}{2\beta + M^2}\right)^{1/2} \tag{33}$$

Equation (37) then yields, for a given set of values of the stream Mach number M_1 and the local Mach number M, a value for the ratio $(q/q_1)_i$ of the local velocity q and the stream velocity q_1 in an incompressible fluid. Table 2 shows corresponding values of $(q/q_1)_c$ and $(q/q_1)_i$ for various values of the stream Mach number M_1 with $\gamma = 1.4$ ($\beta = 2.5$).   This tabulation is performed, for the purpose of comparison, for the three cases represented by equations (35), (36), and (37).   Values of $(q/q_1)_i$, $(q/q_1)_c$, and $\dfrac{(q/q_1)_c}{(q/q_1)_i}$, obtained from equations (37) and (38), are plotted against the local Mach number M in figure 2 for various values of the stream Mach number M_1.   Table 2 also shows values of the pressure coefficients $C_{p,o}$ and C_{p,M_1} calculated by equations (18a) and (18b) for these corresponding values of $(q/q_1)_i$ and $(q/q_1)_c$.   Figure 3 shows the curves of pressure coefficients corresponding to the curves of velocities of figure 2.   Useful cross plots of the curves in figure 3 are shown in figure 4, in which C_{p,M_1} is plotted against M_1 for various values of $C_{p,o}$.   In

addition, curves are shown in figure 4 for $\left(C_{p,M_1}\right)_s$ and and $\left(C_{p,M_1}\right)_m$ calculated by equations (18c) and (18d), respectively.   The curve for $\left(C_{p,M_1}\right)_s$ corresponds to the sonic value $M = 1$ or $\tau = \tau_s = 1/6$ and in effect divides the region of flow into a subsonic and a super- sonic part.   The curve of $\left(C_{p,M_1}\right)_m$ corresponds to the maximum value $M = \infty$ or $\tau = 1$ and represents the outer limit of the supersonic region (or a perfect vacuum). In order to exhibit the main differences between the various correction formulas (35), (36), and (37), the ratios of the sonic values $\left(C_{p,M_1}\right)_s$ and the correspond- ing incompressible values $C_{p,o}$ are plotted against the stream Mach number M_1 in figure 5.

Observe in figure 2 that the $\left(q/q_1\right)_i$-curves have maximum points.   This fact means that the value of $\left(q/q_1\right)_c$ associated with a value of $\left(q/q_1\right)_i$ is not unique.   Analytically, the criterion for the maximum point is equivalent to

$$\frac{d\left(q/q_1\right)_i^2}{d\tau} = 0 \tag{39}$$

or, from velocity correction formula (37),

$$(1 - \tau)^{2\beta+1} - (2\beta + 1)\tau + 1 = 0$$

For $\beta = 2.5$ this equation has only one positive root, $\tau \approx 5/24$ or $M \approx 1.15$.   It is interesting to note that velocity correction formula (36) yields as the criterion for the maximum point

$$1 - (2\beta + 1)\tau = 0$$

The root of this equation is $\tau = \tau_s = \dfrac{1}{2\beta + 1}$ and, for $\beta = 2.5$, is $\tau = 1/6$ or $M = 1$.   Velocity correction formula (35) yields no maximum value of τ or M.

Meaning can be given to the value $\tau = 1/6$ $(M = 1)$ in the case of equation (34) with reference to the original interpretation of the flow pattern as that of a source. It can be shown that the acceleration $\left(q \dfrac{dq}{ds}\right)_c$ along a streamline is infinite at all points for which the local Mach number is unity $(\tau = 1/6)$ and that a flow discontinuity exists there. In the case of the vortex flow pattern (equation (33)), no flow discontinuity occurs for $M < \infty$. The velocity correction formula (37) suggests a "limiting" value $M \approx 1.15$ for a spiral flow, since equation (39) is analogous to a condition of infinite acceleration. Thus, the existence of a mixed subsonic and supersonic region of flow without discontinuities is indicated. Since the occurrence of this limiting value of M is a consequence of the simple form assumed for the velocity correction formula, no undue significance should be attached to any particular value at the present time.

The Chaplygin Approximation

From the point of view of the present paper, Chaplygin's approximation for subsonic speeds assumes a simple and lucid form. Chaplygin introduces in place of q a new independent speed variable η equivalent to the quantity given on the right-hand side of equation (33), namely,

$$\eta = qe^{f(\tau)}$$

The hodograph flow equations (7) then assume the form

$$\left.\begin{aligned} \frac{\partial \phi}{\partial \theta} &= \eta\, \frac{\partial \psi}{\partial \eta} \\ \eta\, \frac{\partial \phi}{\partial \eta} &= -F(\tau)\, \frac{\partial \psi}{\partial \theta} \end{aligned}\right\} \tag{40}$$

where

$$F(\tau) = \frac{1 - (2\beta + 1)\tau}{(1 - \tau)^{2\beta+1}}$$

$$= 1 - \beta(2\beta + 1)\tau^2 - \frac{2}{3}\beta(2\beta + 1)(2\beta + 2)\tau^3 - \ldots$$

Values of the function $F(\tau)$, for several values of γ (or β), are given in table 3 and are plotted in figure 6 against the local Mach number M. Chaplygin noted that, in the case of air ($\beta = 2.5$), $F(\tau)$ differs but little from unity over about one-half the subsonic range $0 \leqq \tau \leqq 1/6$. His approximation in the range of low subsonic speeds consists in neglecting powers of τ higher than the first or in replacing $F(\tau)$ by unity. Equations (40) can then be written in the Cauchy-Riemann form

$$\frac{\partial \phi}{\partial \theta} = \frac{\partial \psi}{\partial \log \eta}$$

$$\frac{\partial \phi}{\partial \log \eta} = - \frac{\partial \psi}{\partial \theta}$$

and $\phi + i\psi$ therefore is an analytic function of the complex variable $\theta + i \log \eta$. Chaplygin's approximation thus leads to the velocity correction formula

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{1 - \frac{5}{4}\tau}{1 - \frac{5}{4}\tau_1} \tag{41}$$

where powers of τ higher than the first are neglected throughout. The use of equation (34) instead of equation (33) also leads to this result to the same order of approximation.

The von Kármán Approximation

Von Kármán's approximation corresponds to the case $\gamma = -1$ $\left(\text{or } \beta = -\frac{1}{2}\right)$. It follows at once from the integral expressions for $f(\tau)$ and $g(\tau)$ given by equations (26) and (27), respectively, that for this case

$$f(\tau) = g(\tau) = - \log \frac{1 + (1 - \tau)^{1/2}}{2}$$

or, with the use of equation (16),

$$f(\tau) = g(\tau) = - \log \frac{1}{2}\left[1 + \frac{1}{(1 - M^2)^{1/2}}\right]$$

This function, plotted against M, is included in figure 1(b). Corresponding to equations (35) and (36), there is a single equation

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{1 + (1 - \tau_1)^{1/2}}{1 + (1 - \tau)^{1/2}}$$

Replacing τ by $\tau_1\left(\frac{q}{q_1}\right)_c^2$ and τ_1 by $\frac{M_1^2}{M_1^2 - 1}$ according to equation (16) yields

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{1 + (1 - M_1^2)^{1/2}}{(1 - M_1^2)^{1/2} + \left[1 - M_1^2 + M_1^2\left(\frac{q}{q_1}\right)_c^2\right]^{1/2}} \quad (42)$$

Then, by solving for $\left(q/q_1\right)_c$ in terms of $\left(q/q_1\right)_i$ and the stream Mach number M_1,

$$\left(\frac{q}{q_1}\right)_c = \left(\frac{q}{q_1}\right)_i \frac{1 - \mu}{1 - \mu\left(\frac{q}{q_1}\right)_i^2} \quad (43)$$

where

$$\mu = \frac{M_1^2}{\left[1 + (1 - M_1^2)^{1/2}\right]^2}$$

The pressure coefficient C_{p,M_1}, expressed in terms of the incompressible pressure coefficient $C_{p,o}$, is easily obtained from the general formula (18b) by putting $\gamma = -1$ and making use of equations (43) and (18a). Thus,

$$C_{p,M_1} = C_{p,o} \frac{1}{\left(1 - M_1^2\right)^{1/2} + \dfrac{M_1^2}{1 + \left(1 - M_1^2\right)^{1/2}} \dfrac{C_{p,o}}{2}} \qquad (44)$$

Observe that for this case the function $F(\tau)$ introduced by Chaplygin and given in equation (40) is exactly equal to unity. From the point of view of the present paper then, von Kármán's approximation appears to be equivalent to that of Chaplygin, who approximates $F(\tau)$ by unity. It follows that the range of validity of von Kármán's approximation and that of Chaplygin, in a strict sense, coincide. Furthermore, it is pointed out that the von Kármán approximation does not permit a supersonic region. Von Kármán's choice of $\gamma = -1$ has the advantage, however, of yielding simple explicit expressions for $\left(q/q_1\right)_c$ in terms of $\left(q/q_1\right)_i$ and for C_{p,M_1} in terms of $C_{p,o}$. Several values of C_{p,M_1} calculated by equation (44) are included in figure 4. For the purpose of comparison with the other approximations, there is plotted in figure 5 the ratio of $\left(C_{p,M_1}\right)_s$ to $C_{p,o}$ against the stream Mach number M_1 in the case of von Kármán's approximation. The values of $C_{p,o}$ are obtained with the use of velocity correction formula (42) for the local Mach number $M = 1$, but the values of $\left(C_{p,M_1}\right)_s$ are calculated with $\gamma = 1.4$.

The Temple-Yarwood Approximation

The functions ϕ and ψ related by the first-order simultaneous equations (21) separately satisfy the second-order equations

$$\frac{\partial^2 \phi}{\partial \theta^2} + \lambda_1(q) \frac{\partial}{\partial q} \left[\frac{1}{\lambda_2(q)} \frac{\partial \phi}{\partial q} \right] = 0$$

$$\frac{\partial^2 \psi}{\partial \theta^2} + \frac{1}{\lambda_2(q)} \frac{\partial}{\partial q} \left[\lambda_1(q) \frac{\partial \psi}{\partial q} \right] = 0$$

(45)

In terms of the nondimensional speed variable τ and with the values of $\lambda_1(q)$ and $\lambda_2(q)$ for the adiabatic case given by equations (25), these equations take the form

$$\frac{1}{4} \frac{(1 - \tau)^\beta}{\tau} \frac{\partial^2 \phi}{\partial \theta^2} + \frac{\partial}{\partial \tau} \left[\frac{\tau(1 - \tau)^{\beta+1}}{1 - (2\beta + 1)\tau} \frac{\partial \phi}{\partial \tau} \right] = 0$$

$$\frac{1}{4} \frac{1 - (2\beta + 1)\tau}{\tau(1 - \tau)^{\beta+1}} \frac{\partial^2 \psi}{\partial \theta^2} + \frac{\partial}{\partial \tau} \left[\frac{\tau}{(1 - \tau)^\beta} \frac{\partial \psi}{\partial \tau} \right] = 0$$

(46)

Formal solutions of these equations were given by Chaplygin in the form of two infinite series

$$\psi = B\theta + \sum_{m=1}^{\infty} B_m \psi_m(\tau) \sin(m\theta + \epsilon_m)$$

$$\phi = -B\phi_0(\tau) - \sum_{m=1}^{\infty} B_m \phi_m(\tau) \cos(m\theta + \epsilon_m)$$

(47)

where the functions $\psi_m(\tau)$ and $\phi_m(\tau)$ are obtained from hypergeometric series and B, B_m, and ϵ_m are arbitrary constants.

A disadvantage of the formal solution, as remarked by Temple and Yarwood, is that it is unsuitable for

numerical computation because the hypergeometric functions involved are complicated and are not tabulated. Temple and Yarwood therefore looked for approximations that are of practical value in calculations of compressible flows. By means of a skillful analysis, they found such approximations and showed that the simplest forms for ψ_m and ϕ_m are of the type

$$\left. \begin{array}{l} \psi_m(\tau) \approx \left[\eta(\tau)\right]^m \\[18pt] \phi_m(\tau) \approx \left[\xi(\tau)\right]^m \\[18pt] \phi_0(\tau) \approx \log \xi(\tau) \end{array} \right\} \qquad (48)$$

where $\eta(\tau)$ and $\xi(\tau)$, independent of the index m, are

$$\eta = \xi = \left(1 - \frac{5}{4}\tau\right)q \qquad (49)$$

Significantly, from the point of view of the analysis of the present paper, the functions η and ξ, approximated by $\left(1 - \frac{5}{4}\tau\right)q$ are none other than the functions defined on the right-hand sides of equations (33) and (34). The approximation of Temple and Yarwood then leads to the same velocity correction relation as was obtained by means of Chaplygin's approximation (equation (41)).

   The velocity and pressure-coefficient correction formulas obtained by Temple and Yarwood are more involved than the explicit expressions (43) and (44) obtained by von Kármán. Replacing ζ in equation (41) by $\tau_1\left(\dfrac{q}{q_1}\right)_c^2$ thus yields

$$\left(\frac{q}{q_1}\right)_i = \left(\frac{q}{q_1}\right)_c \frac{1 - \frac{5}{4}\tau_1\left(\dfrac{q}{q_1}\right)_c^2}{1 - \frac{5}{4}\tau_1} \qquad (50)$$

where

$$\tau_1 = \frac{M_1^2}{5 + M_1^2}$$

The solution of this cubic equation for $(q/q_1)_c$ is

$$\left(\frac{q}{q_1}\right)_c = \left(\frac{q}{q_1}\right)_i 3\left(1 - \frac{5}{4}\tau_1\right)\frac{\cos\frac{1}{3}(\pi + \sigma)}{\cos\sigma} \qquad (51)$$

where

$$\cos\sigma = \frac{3\sqrt{3}}{2}\left(1 - \frac{5}{4}\tau_1\right)\left(\frac{5}{4}\tau_1\right)^{1/2}\left(\frac{q}{q_1}\right)_i$$

and $0 < \sigma \leqq \frac{\pi}{2}$. The pressure coefficient C_{p,M_1} is then calculated by equation (12b). Some values of the pressure coefficient C_{p,M_1} calculated with the aid of equation (51) are shown in figure 4; a curve of $(C_{p,M_1})_s/C_{p,o}$ plotted against M_1 is included in figure 5. It is remarked that, with the use of equation (39), the velocity correction formula (50) yields a limiting value $M \approx 1.35$.

Approximation Based on Geometric Mean of dL and $d\tilde{L}$

Without going into its deep significance in the present paper, it is of interest to introduce another function related to L and $\tilde{L}$ and to the general particular solutions. This function, which like L and $\tilde{L}$ reduces to $\log q$ for $\tau = 0$, is defined by

$$H(\tau) = \int (dL \ d\tilde{L})^{1/2} \qquad (52)$$

It is remarked that $H(\tau)$ is closely related to a function $K(\tau)$ employed by Temple and Yarwood (reference 7) in the determination of their approximation. In the next section, it will be seen that the function

$H(\tau)$ plays an important role in connection with the Prandtl-Glauert approximation.

From equations (26) and (27),

$$dL = \frac{1}{\lambda_1}\, dq = (1 - \tau)^\beta\, \frac{dq}{q}$$

and

$$d\tilde{L} = \lambda_2 dq = \frac{1 - (2\beta + 1)\tau}{(1 - \tau)^{\beta+1}}\, \frac{dq}{q}$$

Then,

$$(dL\ d\tilde{L})^{1/2} = \left(\frac{\lambda_2}{\lambda_1}\right)^{1/2} dq = \left[\frac{1 - (2\beta + 1)\tau}{1 - \tau}\right]^{1/2} \frac{dq}{q} \qquad (53)$$

and, from equation (52),

$$H(\tau) = \log q + h(\tau) \qquad (54)$$

where

$$h(\tau) = \frac{1}{2} \int_0^\tau \left\{ \left[\frac{1 - (2\beta + 1)\tau}{1 - \tau}\right]^{1/2} - 1 \right\} \frac{d\tau}{\tau}$$

The function $h(\tau)$ can be obtained in a closed form for any value of γ (or β) and is

$$h(\tau) = -\log \frac{\left[(1-\tau)^{1/2} + \left(1 - \frac{\tau}{\tau_s}\right)^{1/2}\right]\left[(1-\tau)^{1/2} - (\tau_s-\tau)^{1/2}\right]^{\frac{1}{\sqrt{\tau_s}}}}{2\left(1 - \sqrt{\tau_s}\right)^{\frac{1}{\sqrt{\tau_s}}}} \qquad (55a)$$

and equation (56) may be written as

$$\left(\frac{q}{q_1}\right)_i = \frac{e^{\int (dL \ d\tilde{L})^{1/2}}}{\left[e^{\int (dL \ d\tilde{L})^{1/2}}\right]_{\tau=\tau_1}}$$

Thus, the power of the exponential is in one case the integral of the arithmetic mean $\dfrac{dL + d\tilde{L}}{2}$ and in the other case the integral of the geometric mean $(dL \ d\tilde{L})^{1/2}$. Table 1 shows values of the functions $\dfrac{f(\tau) + g(\tau)}{2}$ and $h(\tau)$ in the case of air ($\gamma = 1.4$, $\beta = 2.5$, and $\tau_s = 1/6$) and figures 1(a) and 1(b) show these functions plotted against τ and M, respectively. Observe that these functions, and consequently the velocity correction formulas (37) and (56), differ only slightly in the subsonic range $0 < M < 1$. Figure 5 exhibits graphically a comparison of the velocity correction formulas (37) and (56) for $M = 1$. The limiting value of M (defined by equation (39)) is $M = 1$ in the case of equation (56) as compared with $M \approx 1.15$ in the case of equation (37).

Comparison of Results of Present Paper

with Prandtl-Glauert Approximation

The well-known Prandtl-Glauert approximation is based on the assumption of vanishingly small disturbances to the main stream. The Prandtl-Glauert velocity correction formula may be expressed as

$$\frac{\left(\dfrac{q - q_1}{q_1}\right)_c}{\left(\dfrac{q - q_1}{q_1}\right)_i} = \frac{1}{\left(1 - M_1^2\right)^{1/2}} \tag{57}$$

where $q - q_1$ is vanishingly small. The left-hand side

of this equation is actually the differential coeffi-
cient $\dfrac{d(q/q_1)_c}{d(q/q_1)_i}$ evaluated at the main stream velocity
$q = q_1$ (or $\tau = \tau_1$). An exact form of the Prandtl-
Glauert approximation then is

$$\left[\frac{d(q/q_1)_c}{d(q/q_1)_i}\right]_{\tau=\tau_1} = \frac{1}{\left(1 - M_1^2\right)^{1/2}} \tag{58}$$

The differential coefficient in equation (58) is now
evaluated for the various approximations treated in the
present paper.

For the arithmetic-mean approximation of the
present paper given by equation (37) (γ or β arbi-
trary),

$$\left[\frac{d(q/q_1)_c}{d(q/q_1)_i}\right]_{\tau=\tau_1} = \frac{2}{\left(1 - \tau_1\right)^{\beta} + \dfrac{1 - (2\beta + 1)\tau_1}{\left(1 - \tau_1\right)^{\beta+1}}}$$

$$= \frac{2\left(1 + \dfrac{M_1^2}{2\beta}\right)^{\beta}}{1 + \left(1 - M_1^2\right)\left(1 + \dfrac{M_1^2}{2\beta}\right)^{2\beta}}$$

$$= 1 + \frac{1}{2} M_1^2 + \frac{3}{8} M_1^4 + \frac{5}{16} M_1^6$$

$$+ \frac{5}{128} \frac{11\beta^2 + 4\beta + 1}{\beta^2} M_1^8 + \cdots \tag{59}$$

For the Chaplygin or the Temple-Yarwood approximation given by equation (41) ($\gamma = 1.4$ or $\beta = 2.5$),

$$\left[\frac{d\left(q/q_1\right)_c}{d\left(q/q_1\right)_i}\right]_{\tau=\tau_1} = \frac{1 - \frac{5}{4}\,\tau_1}{1 - \frac{15}{4}\,\tau_1}$$

$$= \frac{1 - \frac{1}{20}\,M_1^2}{1 - \frac{11}{20}\,M_1^2}$$

$$= 1 + \frac{1}{2}\,M_1^2 + \frac{11}{40}\,M_1^4 + \ldots \qquad (60)$$

· For the von Kármán approximation given by equation (42) $\left(\gamma = -1 \quad \text{or} \quad \beta = -\frac{1}{2}\right)$,

$$\left[\frac{d\left(q/q_1\right)_c}{d\left(q/q_1\right)_i}\right]_{\tau=\tau_1} = (1 - \tau)^{1/2}$$

$$= \frac{1}{\left(1 - M_1^2\right)^{1/2}} \qquad (61)$$

For the geometric-mean approximation of the present paper given by equation (56) (γ or β arbitrary),

$$\left[\frac{d\left(q/q_1\right)_c}{d\left(q/q_1\right)_i}\right]_{\tau=\tau_1} = \left[\frac{1 - \tau_1}{1 - (2\beta + 1)\tau_1}\right]^{1/2}$$

$$= \frac{1}{\left(1 - M_1^2\right)^{1/2}} \qquad (62)$$

Equation (62) is independent of the value of the adiabatic index γ and includes the von Kármán approximation. Observe that the geometric-mean approximation yields the Prandtl-Glauert result exactly, whereas the arithmetic-mean approximation yields the Prandtl-Glauert

result insofar as terms inclusive of M_1^6 are concerned.
The Chaplygin or the Temple-Yarwood approximation con-
tains the Prandtl-Glauert result only insofar as the M_1^2
term is concerned.

RÉSUMÉ AND CONCLUDING REMARKS

1. Basic elementary solutions of the hodograph equa-
tions have been employed to provide a basis for comparison,
in the form of velocity correction formulas, of corre-
sponding compressible and incompressible flows.

2. The velocity correction formulas obtained by
Chaplygin, by von Kármán, and by Temple and Yarwood have
been unified by means of these basic solutions and shown
to be essentially equivalent.

3. In the present paper two types of approximations
have been introduced by means of the basic elementary
solutions, namely, the "arithmetic-mean" type and the
"geometric-mean" type. These approximations include
those obtained by Chaplygin, by von Kármán, and by Temple
and Yarwood.

4. The approximations discussed in the present paper
have been compared with the well-known results of Prandtl
and Glauert. For this purpose, it has been emphasized
that the Prandtl-Glauert result is valid for vanishingly
small disturbances and, in a strict sense, is the slope
term in a Taylor expansion in a quantity which measures
the disturbance. It was found that the arithmetic-mean
type yields the Prandtl-Glauert result to a higher order
of approximation than the Chaplygin or the Temple-Yarwood
type and that the geometric-mean type contains the
Prandtl-Glauert result exactly. The two types of approxi-
mations introduced in the present paper then appear to be
preferable to the others as a basis for extrapolation into
the range of high stream Mach numbers and large disturb-
ances to the main stream.

5. The results of the present paper have been ob-
tained without consideration of any particular boundary.
The actual boundary problem of determining the flow past
a prescribed body is of a high order of difficulty and
involves in general all the particular solutions of the
hodograph equations.

6. The particular solutions discussed in the present
paper are well-behaved functions in both the subsonic and
the supersonic regions. The hodograph equations give no
reason, in general, to suppose that a discontinuity neces-
sarily occurs in the solution when local sound speed is
attained. Rather, it appears that the first breakdown of
the solution is associated with the vanishing of the
Jacobian of the transformation from the physical to the
hodograph variables. Indeed, von Kármán has made an equi-
valent suggestion in that the appearance of infinite accel-
erations in the flow solution is a condition for flow dis-
continuities. Interesting speculations on this matter are
suggested by the results of the present paper since the
"limiting" curves discussed in the present paper are
defined by a condition that is equivalent to the condition
for infinite acceleration. The arithmetic-mean type of
approximation thus yields a limiting value of the local
Mach number $M \approx 1.15$, and the geometric-mean type of
approximation yields a limiting value of the local Mach
number $M = 1$. The value $M = 1$ appears to be exact for
vanishingly small disturbances; that is, local Mach
number M = stream Mach number $M_1 = 1$ (Prandtl-Glauert
approximation). However, for finite disturbances to the
main flow due to the presence of a body in the fluid,
infinite accelerations may occur, for stream Mach numbers
less than unity, in regions where the local Mach number
is greater than unity. In this regard, the arithmetic-
mean type of approximation, considered as an extension of
the Prandtl-Glauert relation to finite disturbances, indi-
cates the possibility of a mixed subsonic and supersonic
flow without discontinuities. It is important, however,
to recognize that in general the limiting value of the
local Mach number M is a function of shape parameters
and is a result of the blending of many particular solu-
tions of the hodograph flow equations according to the
boundary conditions.

Langley Memorial Aeronautical Laboratory,
      National Advisory Committee for Aeronautics,
            Langley Field, Va.

REFERENCES

1. Molenbroek, P.: Über einige Bewegungen eines Gases
    mit Annahme eines Geschwindigkeitspotentials.
    Archiv d. Math. u. Phys. (2), vol. 9, 1890, p. 157.

2. Chaplygin, S. A.: On Gas Jets.   (Text in Russian.)
    Sci. Ann., Moscow Imperial Univ., Math.-Phys. Sec.,
    vol. 21, 1904, pp. 1-121.

3. Demtchenko, B.: Quelques problèmes d'hydrodynamique
    bidimensionelle des fluides compressibles.   Pub.
    No. 144, Pub. Sci. et Tech. du Ministère de l'air
    (Paris), 1939.

4. von Kármán, Th.: Compressibility Effects in Aero-
    dynamics.   Jour. Aero. Sci., vol. 8, no. 9,
    July 1941, pp. 337-356.

5. Tsien, Hsue-Shen: Two-Dimensional Subsonic Flow of
    Compressible Fluids.   Jour. Aero. Sci., vol. 6,
    no. 10, Aug. 1939, pp. 399-407.

6. Ringleb, Friedrich: Exakte Lösungen der Differential-
    gleichungen einer adiabatischen Gasströmung.
    Z.f.a.M.M., Bd. 20, Heft 4, Aug. 1940, pp. 185-198.

7. Temple, G., and Yarwood, J.: The Approximate Solution
    of the Hodograph Equations for Compressible Flow.
    Rep. No. S.M.E. 3201, R.A.E., June 1942.

8. Bers, Lipman, and Gelbart, Abe: On a Class of Dif-
    ferential Equations in Mechanics of Continua.
    Quarterly Appl. Math., vol. I, no. 2, July 1943,
    pp. 168-188.

9. Hilbert, David: Grundzüge einer allgemeinen Theorie
    der linearen Integralgleichungen.   B. G. Teubner
    (Leipzig and Berlin), 1924, p. 73.

TABLE 1.- VALUES OF f, g, $\frac{1}{2}(f+g)$, h, AND THEIR EXPONENTIALS FOR $\gamma = 1.4$

M	τ	f	g	$\frac{1}{2}(f+g)$	h	e^f	e^g	$e^{\frac{1}{2}(f+g)}$	e^h
0	0	0	0	0	0	1.00	1.00	1.00	1.00
.1	.00200	-.00250	-.00251	-.00251	-.00250	.99750	.99749	.99750	.99750
.2	.00794	-.00989	-.01013	-.01001	-.01001	.99016	.98992	.99004	.99004
.3	.01768	-.02196	-.02316	-.02256	-.02256	.97828	.97711	.97769	.97769
.4	.03101	-.03831	-.04208	-.04020	-.04020	.96241	.95879	.96060	.96060
.5	.04762	-.05847	-.06760	-.06304	-.06306	.94321	.93463	.93890	.93889
.6	.06716	-.08186	-.10059	-.09123	-.09133	.92140	.90430	.91281	.91271
.65	.07792	-.09457	-.12023	-.10740	-.10768	.90977	.88671	.89817	.89792
.70	.08925	-.10787	-.14216	-.12502	-.12541	.89775	.86748	.88248	.88213
.75	.10112	-.12167	-.16657	-.14412	-.14484	.88544	.84656	.86578	.86516
.80	.11348	-.13588	-.19363	-.16476	-.16605	.87295	.82397	.84810	.84700
.825	.11982	-.14313	-.20822	-.17568	-.17740	.86664	.81202	.83889	.83744
.850	.12626	-.15045	-.22354	-.18700	-.18927	.86032	.79968	.82944	.82756
.875	.13279	-.15785	-.23964	-.19875	-.20173	.85398	.78691	.81975	.81732
.900	.13942	-.16530	-.25652	-.21091	-.21487	.84764	.77374	.80985	.80664
.925	.14612	-.17281	-.27423	-.22352	-.22876	.84130	.76016	.79969	.79552
.950	.15290	-.18036	-.29280	-.23658	-.24353	.83497	.74617	.78953	.78386
.96	.15563	-.18339	-.30047	-.24193	-.24976	.83245	.74047	.78511	.77899
.98	.16113	-.18946	-.31624	-.25285	-.26292	.82741	.72888	.77658	.76880
1.00	.16667	-.19556	-.33261	-.26409	-.27757	.82237	.71705	.76791	.75762
1.02	.17224	-.20166	-.34958	-.27562	------	.81737	.70498	.75910	------
1.04	.17785	-.20778	-.36718	-.28748	------	.81239	.69268	.75015	------
1.06	.18349	-.21391	-.38542	-.29967	------	.80742	.68017	.74106	------
1.08	.18915	-.22003	-.40432	-.31218	------	.80250	.66743	.73185	------
1.10	.19485	-.22616	-.42390	-.32503	------	.79759	.65449	.72251	------
1.12	.20056	-.23228	-.44417	-.33823	------	.79273	.64136	.71303	------
1.15	.20917	-.24144	-.47594	-.35869	------	.78550	.62130	.69859	------
1.18	.21782	-.25059	-.50938	-.37999	------	.77834	.60087	.68387	------
1.20	.22360	-.25665	-.53263	-.39464	------	.77564	.58706	.67392	------
1.30	.25262	-.28673	-.66139	-.47406	------	.75072	.51613	.62247	------
1.40	.28161	-.31604	-.81292	-.56448	------	.72903	.44356	.56865	------
1.50	.31034	-.34438	-.99030	-.66734	------	.70866	.37147	.51307	------
2.00	.44444	-.46775	-2.39742	-1.43259	------	.62641	.09095	.23869	------
2.50	.55556	-.55925	-5.12014	-2.85970	------	.57164	.00598	.05844	------
3.00	.64286	-.62470	-9.99177	-5.30024	------	.53542	.00004	.00495	------
4.00	.76190	-.70538	-31.27238	-15.98888	------	.49392	.00000	.00000	------
5.00	.83333	-.74934	-80.81740	-40.78537	------	.47268	.00000	.00000	------
∞	1.00	-.84019	$-\infty$	$-\infty$	------	.43162	0	.00000	------

TABLE 2.- VALUES OF $(q/q_1)_c$, $(q/q_1)_1$, $\dfrac{(q/q_1)_c}{(q/q_1)_1}$, $C_{p,o}$, AND C_{p,M_1}

FOR $\gamma = 1.4$ AND FOR VARIOUS VALUES OF M_1

NATIONAL ADVISORY
COMMITTEE FOR AERONAUTICS

M		0.2	0.3	0.4	0.5	0.55	0.6	0.7	0.8	0.9	1.0	1.1	1.2
τ		0.00794	0.01766	0.03101	0.04762	0.05705	0.06716	0.08928	0.11348	0.13942	0.16667	0.19485	0.22360
$M_1 = 0.2$													
$(q/q_1)_c$		1.00	1.49262	1.97660	2.44948	2.68106	2.90907	3.35349	3.78124	4.19121	4.58256	4.96484	5.30790
$(q/q_1)_1$	Eq. (36)	1.00	1.47471	1.92120	2.33332	2.52518	2.70708	3.04061	3.33366	3.58793	3.80699	3.99122	4.14789
	Eq. (36)	1.00	1.47331	1.91444	2.31268	2.49242	2.65748	2.93870	3.14735	3.27593	3.31937	3.27590	3.16780
	Eq. (37)	1.00	1.47401	1.91782	2.32296	2.60876	2.68213	2.98917	3.23912	3.42841	3.55441	3.61694	3.61309
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		1.00	1.01263	1.03065	1.05446	1.06868	1.08461	1.12188	1.16737	1.22249	1.28926	1.37026	1.46907
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0	-1.17271	-2.67803	-4.39614	-5.29383	-6.19382	-7.93614	-9.49190	-10.75400	-11.63383	-12.07502	-12.05442
C_{p,M_1} (Eq. (18b))		0	-1.21250	-2.82393	-4.78500	-5.81893	-6.92214	-9.23893	-11.62214	-14.00071	-15.31387	-18.61393	-20.57000
$M_1 = 0.3$													
$(q/q_1)_c$		0.66097	1.00	1.32425	1.64107	1.79621	1.94898	2.24672	2.53331	2.80797	3.07016	3.31988	3.55612
$(q/q_1)_1$	Eq. (36)	0.67810	1.00	1.30277	1.58224	1.71233	1.83567	2.06177	2.26066	2.45299	2.58087	2.70646	2.81296
	Eq. (36)	0.67875	1.00	1.29942	1.56971	1.69172	1.80374	1.99483	2.13628	2.22356	2.25504	2.22353	2.13653
	Eq. (37)	0.67843	1.00	1.30110	1.57396	1.70300	1.81965	2.02793	2.19782	2.32693	2.41140	2.45317	2.45123
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.98763	1.00	1.01779	1.04131	1.05636	1.07107	1.10789	1.15280	1.20725	1.27315	1.35318	1.46075
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.53973	0	-0.69285	-1.48366	-1.89680	-2.51113	-3.11250	-3.82909	-4.40996	-4.81485	-5.01804	-6.00853
C_{p,M_1} (Eq. (18b))		0.55794	0	-0.74111	-1.62984	-2.11683	-2.62651	-3.69238	-4.78921	-5.88302	-6.94746	-7.85968	-8.90871
$M_1 = 0.4$													
$(q/q_1)_c$		0.50692	0.75514	1.00	1.23924	1.36640	1.47174	1.69659	1.91300	2.12040	2.31840	2.50876	2.68536
$(q/q_1)_1$	Eq. (36)	0.52051	0.76759	1.00	1.21651	1.31438	1.40903	1.56260	1.73519	1.86754	1.98105	2.07744	2.13863
	Eq. (36)	0.52236	0.76987	1.00	1.20801	1.30190	1.38811	1.53503	1.64401	1.71116	1.73587	1.71116	1.64492
	Eq. (37)	0.52143	0.76857	1.00	1.21126	1.30613	1.39663	1.55863	1.68897	1.78766	1.85336	1.86542	1.88594
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.97025	0.98263	1.00	1.02312	1.03690	1.05238	1.08852	1.13264	1.18514	1.25092	1.32954	1.42540
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.72811	0.40930	0	-0.46710	-0.71120	-0.96689	-1.48930	-1.85262	-2.19569	-2.43494	-2.55451	-2.64923
C_{p,M_1} (Eq. (18b))		0.76663	0.43714	0	-0.52420	-0.81186	-1.11269	-1.74182	-2.38866	-3.03429	-3.66208	-4.25938	-4.81780
$M_1 = 0.5$													
$(q/q_1)_c$		0.40825	0.60936	0.80696	1.00	1.09454	1.18763	1.36906	1.54370	1.71106	1.87084	2.02281	2.16694
$(q/q_1)_1$	Eq. (36)	0.42867	0.63202	0.82338	1.00	1.08222	1.16017	1.30307	1.42871	1.53749	1.63116	1.71061	1.77737
	Eq. (36)	0.43240	0.63706	0.82781	1.00	1.07773	1.14909	1.27069	1.36092	1.41652	1.43631	1.41651	1.36110
	Eq. (37)	0.43049	0.63464	0.82660	1.00	1.07998	1.15462	1.28479	1.39440	1.47688	1.53012	1.55662	1.55839
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.94836	0.96032	0.97741	1.00	1.01348	1.02859	1.06393	1.10707	1.16936	1.22267	1.29941	1.39316
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.81468	0.59736	0.31838	0	-0.16636	-0.33315	-0.65583	-0.94435	-1.17822	-1.34127	-1.42507	-1.61924
C_{p,M_1} (Eq. (18b))		0.87771	0.65366	0.35646	0	-0.19554	-0.40000	-0.82766	-1.26784	-1.70667	-2.13343	-2.53960	-2.91903
$M_1 = 0.55$													
$(q/q_1)_c$		0.37299	0.56672	0.73726	0.91363	1.00	1.08504	1.25081	1.41056	1.56326	1.70923	1.84810	1.97978
$(q/q_1)_1$	Eq. (36)	0.39601	0.58399	0.76083	0.92604	1.00	1.07202	1.20408	1.32017	1.42086	1.50722	1.58057	1.64835
	Eq. (36)	0.40122	0.59110	0.76811	0.92788	1.00	1.06621	1.17906	1.26278	1.31434	1.33178	1.31435	1.26296
	Eq. (37)	0.39861	0.58755	0.76446	0.92695	1.00	1.06911	1.19150	1.29114	1.36667	1.41680	1.44133	1.44019
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.93573	0.94766	0.96441	0.98669	1.00	1.01490	1.04978	1.09234	1.14393	1.20640	1.28222	1.37467
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.84111	0.65481	0.41580	0.16262	0	-0.16300	-0.61967	-0.66704	-0.86751	-1.00732	-1.07743	-1.07418
C_{p,M_1} (Eq. (18b))		0.91835	0.72685	0.47249	0.16757	0	-0.17497	-0.66078	-0.91751	-1.29299	-1.65628	-2.00590	-2.33058

TABLE 2.- Continued

M		0.4	0.6	0.65	0.7	0.75	0.8	0.85	0.9	1.0	1.1	1.2	1.3
τ		0.03101	0.06718	0.07792	0.08925	0.10112	0.11348	0.12626	0.13942	0.16687	0.19485	0.22360	0.25262
$M_1 = 0.6$													
$(q/q_1)_c$		0.87947	1.00	1.07707	1.15277	1.22704	1.29981	1.37107	1.44093	1.57527	1.70324	1.82460	1.93939
$(q/q_1)_1$	Eq. (35)	0.70971	1.00	1.06348	1.12318	1.17914	1.23148	1.28018	1.32559	1.40596	1.47438	1.53201	1.58014
	Eq. (36)	0.72041	1.00	1.05812	1.10583	1.14869	1.18435	1.21245	1.23289	1.24908	1.23272	1.18451	1.10891
	Eq. (37)	0.71504	1.00	1.05979	1.11447	1.16362	1.20787	1.24585	1.27841	1.32521	1.34815	1.34708	1.32253
$\frac{(q/q_1)_c}{(q/q_1)_1}$		0.95025	1.00	1.01631	1.03437	1.05432	1.07630	1.10051	1.12713	1.18869	1.26339	1.35449	1.46642
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.48872	0	-0.12315	-0.24204	-0.35448	-0.45847	-0.55214	-0.63433	-0.75618	-0.81751	-0.81462	-0.74909
C_{p,M_1} (Eq. (18b))		0.56492	0	-0.18786	-0.31929	-0.48310	-0.84774	-0.81238	-0.97599	-1.29437	-1.59762	-1.88099	-2.14151
$M_1 = 0.65$													
$(q/q_1)_c$		0.83084	0.92843	1.00	1.07029	1.13924	1.20681	1.27296	1.33785	1.46255	1.58138	1.69405	1.80060
$(q/q_1)_1$	Eq. (35)	0.86734	0.94030	1.00	1.05615	1.10878	1.15797	1.20377	1.24630	1.32204	1.38638	1.44057	1.48582
	Eq. (36)	0.68212	0.94685	1.00	1.04708	1.08756	1.12142	1.14802	1.15723	1.18271	1.15723	1.12158	1.04808
	Eq. (37)	0.67469	0.94356	1.00	1.05159	1.09816	1.13953	1.17555	1.20612	1.25044	1.27209	1.27110	1.24789
$\frac{(q/q_1)_c}{(q/q_1)_1}$		0.93501	0.98395	1.00	1.01778	1.03741	1.05904	1.08286	1.10906	1.18963	1.24314	1.33274	1.44292
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.84479	0.10969	0	-0.10584	-0.20596	-0.29853	-0.38192	-0.48473	-0.56360	-0.61821	-0.61570	-0.55723
C_{p,M_1} (Eq. (18b))		0.84074	0.14002	0	-0.14333	-0.28862	-0.43476	-0.88086	-0.72571	-1.00862	-1.27767	-1.52913	-1.76024
$M_1 = 0.7$													
$(q/q_1)_c$		0.58942	0.86747	0.93433	1.00	1.06442	1.12758	1.18936	1.24980	1.36550	1.47752	1.58280	1.68235
$(q/q_1)_1$	Eq. (35)	0.63186	0.89032	0.94683	1.00	1.04983	1.09641	1.13978	1.18003	1.25175	1.31266	1.36398	1.40681
	Eq. (36)	0.65146	0.90429	0.95504	1.00	1.03875	1.07099	1.09640	1.11475	1.12953	1.11475	1.07114	1.00098
	Eq. (37)	0.64159	0.89728	0.95094	1.00	1.04429	1.08362	1.11788	1.14695	1.18909	1.20959	1.20874	1.18665
$\frac{(q/q_1)_c}{(q/q_1)_1}$		0.91869	0.96878	0.98253	1.00	1.01928	1.04056	1.06394	1.08967	1.14920	1.22140	1.30945	1.41772
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.58836	0.19489	0.09571	0	-0.09054	-0.17423	-0.24966	-0.31549	-0.41394	-0.46335	-0.46105	-0.40818
C_{p,M_1} (Eq. (18b))		0.70580	0.25516	0.12904	0	-0.13082	-0.26254	-0.39397	-0.52440	-0.77907	-1.02140	-1.24781	-1.45589
$M_1 = 0.75$													
$(q/q_1)_c$		0.55374	0.81497	0.87778	0.93947	1.00	1.05931	1.11737	1.17416	1.28380	1.38810	1.48701	1.58054
$(q/q_1)_1$	Eq. (35)	0.60187	0.84807	0.90191	0.95253	1.00	1.04436	1.08568	1.12404	1.19235	1.25038	1.29926	1.34006
	Eq. (36)	0.62715	0.87055	0.91942	0.96968	1.00	1.03105	1.05550	1.07317	1.08740	1.07317	1.03120	0.96362
	Eq. (37)	0.61439	0.85924	0.91062	0.95759	1.00	1.03768	1.07047	1.09831	1.13888	1.15840	1.15749	1.13636
$\frac{(q/q_1)_c}{(q/q_1)_1}$		0.90128	0.94848	0.96394	0.98108	1.00	1.02084	1.04381	1.06906	1.12745	1.19829	1.28468	1.39088
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.62252	0.26171	0.17077	0.08302	0	-0.07678	-0.14591	-0.20628	-0.29659	-0.34189	-0.33978	-0.29131
C_{p,M_1} (Eq. (18b))		0.76361	0.35197	0.23700	0.11937	0	-0.12005	-0.23997	-0.35893	-0.59124	-0.81227	-1.01872	-1.20853
$M_1 = 0.8$													
$(q/q_1)_c$		0.52274	0.76934	0.82864	0.88687	0.94402	1.00	1.05482	1.10842	1.21193	1.31038	1.40375	1.49204
$(q/q_1)_1$	Eq. (35)	0.57631	0.81205	0.86359	0.91207	0.95753	1.00	1.03956	1.07629	1.14171	1.19725	1.24405	1.28312
	Eq. (36)	0.60827	0.84435	0.89172	0.93371	0.96990	1.00	1.02372	1.04085	1.05487	1.04086	1.00014	0.93460
	Eq. (37)	0.59209	0.82805	0.87756	0.92283	0.96370	1.00	1.03162	1.05843	1.09734	1.11633	1.11545	1.09610
$\frac{(q/q_1)_c}{(q/q_1)_1}$		0.88287	0.92910	0.94425	0.96103	0.97958	1.00	1.02249	1.04723	1.10443	1.17383	1.25846	1.36247
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.64943	0.31433	0.22989	0.14838	0.07128	0	-0.06424	-0.12027	-0.20416	-0.24619	-0.24423	-0.19984
C_{p,M_1} (Eq. (18b))		0.81520	0.43547	0.32940	0.22083	0.11074	0	-0.11065	-0.22036	-0.43464	-0.63857	-0.82904	-1.00411

TABLE 2.- Concluded

M		0.4	0.6	0.825	0.85	0.875	0.9	0.925	0.96	1.0	1.1	1.2	1.3
τ		0.03101	0.06716	0.11982	0.12626	0.13279	0.13942	0.14612	0.15563	0.16667	0.19485	0.22360	0.25262
$M_1 = 0.825$													
$(q/q_1)_c$		0.50872	0.74871	1.00	1.02653	1.05276	1.07870	1.10434	1.13972	1.17942	1.27524	1.36610	1.45203
$(q/q_1)_1$	Eq. (35)	0.56494	0.79602	1.00	1.01905	1.03738	1.05506	1.07205	1.09475	1.11917	1.17363	1.21950	1.25781
	Eq. (36)	0.60068	0.83380	1.00	1.01093	1.02021	1.02785	1.03380	1.03929	1.04147	1.02784	0.98764	0.92292
	Eq. (37)	0.68253	0.81469	1.00	1.01497	1.02874	1.04138	1.05273	1.06665	1.07962	1.09833	1.09746	1.07744
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.87329	0.91901	1.00	1.01139	1.02335	1.03586	1.04902	1.06850	1.09244	1.16107	1.24478	1.34767
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.66066	0.33628	0	-0.03016	-0.05831	-0.08443	-0.10824	-0.13774	-0.16558	-0.20833	-0.20442	-0.16088
C_{p,M_2} (Eq. (18b))		0.83950	0.47350	0	-0.05329	-0.10631	-0.15910	-0.21149	-0.28409	-0.36571	-0.56234	-0.74599	-0.91487
$M_1 = 0.85$													
$(q/q_1)_c$		0.49558	0.72938	0.97416	1.00	1.02555	1.05082	1.07580	1.11026	1.14894	1.24228	1.33080	1.41451
$(q/q_1)_1$	Eq. (35)	0.55438	0.78114	0.98132	1.00	1.01799	1.03532	1.05202	1.07430	1.09826	1.15171	1.19672	1.23432
	Eq. (36)	0.59418	0.82478	0.98920	1.00	1.00917	1.01673	1.02264	1.02805	1.03023	1.01673	0.97697	0.91295
	Eq. (37)	0.57394	0.80267	0.98526	1.00	1.01357	1.02599	1.03721	1.05091	1.06371	1.08212	1.08128	1.06155
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.86347	0.90867	0.98873	1.00	1.01182	1.02420	1.03721	1.05647	1.08013	1.14801	1.23076	1.33249
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.67059	0.35572	0.02926	0	-0.02732	-0.05266	-0.07580	-0.10441	-0.13148	-0.17098	-0.16917	-0.12689
C_{p,M_1} (Eq. (18b))		0.86288	0.50895	0.05147	0	-0.05129	-0.10226	-0.16294	-0.22305	-0.30199	-0.49202	-0.66952	-0.83274
$M_1 = 0.875$													
$(q/q_1)_c$		0.48322	0.71118	0.94988	0.97508	1.00	1.02463	1.04898	1.08259	1.12031	1.21133	1.29763	1.37926
$(q/q_1)_1$	Eq. (35)	0.54458	0.76734	0.96396	0.98232	1.00	1.01703	1.03340	1.05550	1.07865	1.13134	1.17555	1.21248
	Eq. (36)	0.58877	0.81727	0.98020	0.99091	1.00	1.00748	1.01333	1.01870	1.02085	1.00749	0.96807	0.90464
	Eq. (37)	0.56826	0.79192	0.97207	0.98661	1.00	1.01225	1.02331	1.03684	1.04947	1.06764	1.06678	1.04733
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.85335	0.89805	0.97717	0.98831	1.00	1.01223	1.02509	1.04412	1.06750	1.13459	1.21640	1.31693
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.67935	0.37286	0.05508	0.02660	0	-0.02465	-0.04716	-0.07504	-0.10139	-0.13986	-0.13802	-0.09690
C_{p,M_1} (Eq. (18b))		0.88564	0.54277	0.09960	0.04971	0	-0.04943	-0.09848	-0.16642	-0.24286	-0.42701	-0.59898	-0.75712
$M_1 = 0.9$													
$(q/q_1)_c$		0.47160	0.69409	0.92705	0.95164	0.97595	1.00	1.02376	1.05657	1.09338	1.18220	1.26644	1.34609
$(q/q_1)_1$	Eq. (35)	0.53546	0.75449	0.94783	0.96587	0.98525	1.00	1.01610	1.03764	1.06079	1.11240	1.15588	1.19218
	Eq. (36)	0.58439	0.81121	0.97291	0.98355	0.99257	1.00	1.00579	1.01113	1.01327	1.00000	0.96089	0.89792
	Eq. (37)	0.55939	0.78233	0.96029	0.97466	0.98786	1.00	1.01091	1.02429	1.03676	1.05470	1.05387	1.03463
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.84308	0.88721	0.96539	0.97638	0.98792	1.00	1.01271	1.03151	1.05461	1.12089	1.20170	1.30104
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.68708	0.38798	0.07784	0.05004	0.02409	0	-0.02194	-0.04917	-0.07487	-0.11239	-0.11064	-0.07046
C_{p,M_1} (Eq. (18b))		0.90787	0.57490	0.14460	0.09617	0.04799	0	-0.04762	-0.11365	-0.18788	-0.36660	-0.53362	-0.68711
$M_1 = 0.925$													
$(q/q_1)_c$		0.46088	0.67798	0.90552	0.92965	0.95331	0.97678	1.00	1.03205	1.06800	1.15476	1.23704	1.31486
$(q/q_1)_1$	Eq. (35)	0.52697	0.74253	0.93279	0.95057	0.96768	0.98415	1.00	1.02119	1.04397	1.09476	1.13756	1.17329
	Eq. (36)	0.58103	0.80654	0.96729	0.97787	0.98686	0.99423	1.00	1.00532	1.00743	0.99424	0.95534	0.89276
	Eq. (37)	0.55335	0.77387	0.94991	0.96413	0.97721	0.98919	1.00	1.01323	1.02556	1.04332	1.04249	1.02347
$\dfrac{(q/q_1)_c}{(q/q_1)_1}$		0.83249	0.87609	0.95327	0.96413	0.97554	0.98745	1.00	1.01857	1.04138	1.10681	1.18662	1.28471
$C_{p,o}$ (Eq. (18a))	Eq. (37)	0.69380	0.40113	0.09767	0.07045	0.04506	0.02150	0	-0.02664	-0.05177	-0.08852	-0.08679	-0.04749
C_{p,M_1} (Eq. (18b))		0.92963	0.60574	0.18708	0.13991	0.09301	0.04633	0	-0.06425	-0.13642	-0.31038	-0.47285	-0.62222

TABLE 3.- VALUES OF F(τ) FOR SEVERAL VALUES OF γ

$$F(\tau) = \frac{1 - (2\beta + 1)\tau}{(1 - \tau)^{2\beta+1}} = \frac{1 - M^2}{\left(1 + \frac{M^2}{2\beta}\right)^{-2\beta}}$$

M	F			
	$\gamma = 1.4$ ($\beta = 2.5$) Adiabatic	$\gamma = 1$ ($\beta \rightarrow \infty$) Isothermal (1)	$\gamma = 2$ ($\beta = 1$) Hydraulic analogy	$\gamma = \infty$ ($\beta \rightarrow 0$) Limiting incompressible (2)
0	1.00	1.00	1.00	1.00
.2	.99901	.99918	.99879	.9600
.4	.98328	.98575	.97977	.8400
.6	.90606	.91733	.89113	.6400
.65	.86634	.88113	.84726	.5775
.70	.81394	.83248	.79050	.5100
.75	.74558	.76783	.71822	.4375
.80	.65738	.68273	.62728	.3600
.85	.54489	.57153	.51421	.2775
.90	.40258	.42710	.37504	.1900
.95	.22355	.24041	.20534	.0975
1.00	0	0	0	0
1.05	-.27752	-.30870	-.24667	-.1025
1.10	-.62069	-.70423	-.54102	-.2100
1.20	-1.55960	-1.85711	-1.30158	-.4400
1.30	-2.95915	-3.73944	-2.34862	-.6900
1.50	-8.01227	-11.8597	-5.64466	-1.2500
2.00	-56.6884	-163.79	-26.9981	-3.0000

1 $\gamma = 1$, $F = (1 - M^2)e^{M^2}$

2 $\gamma = \infty$, $F = 1 - M^2$

(a) τ-curves

Figure l.- The functions f, g, f+g/2, and h against τ and M for γ=1.4; the function f=g against M for γ=-1.0.

(b) M - curves.

Figure 1. - Concluded.

(a) $(q/q_1)_c$, ratio of local velocity to stream velocity, compressible.

(b) $(q/q_1)_i$, ratio of local velocity to stream velocity, incompressible.

Figure 2.- Velocity ratios $(q/q_1)_c$, $(q/q_1)_i$, and $(q/q_1)_c/(q/q_1)_i$, against local Mach number for various values of stream Mach number M_1. Corresponding values of $(q/q_1)_c$ and $(q/q_1)_i$ in (a) and (b) are given by the same pair of values M, M_1.

(c) curves of $(q/q_1)_c / (q/q_1)_i$.

Figure 2.- concluded.

Figure 3.- Pressure coefficients C_{PM} and C_{PO} against local Mach number M for various values of stream Mach number M_1. Corresponding values of C_{PM} and C_{PO} in (a) and (b) are given by the same pair of values M, M_1.

(a) C_{PM}-curves.

(b) C_{PO}-curves.

Figure 4.- Pressure coefficient $C_{p,M}$ against stream Mach number M_1 with corresponding values of $C_{p,0}$; and lines of constant local Mach number M.

Figure 5. - The ratio of $(C_{BM})_s$ to $C_{p,o}$ against M_1 for the various approximations.

Figure 6. — The function F against Mach number M for several values of the adiabatic index γ.

NATIONAL ADVISORY
COMMITTEE FOR AERONAUTICS